



MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SDS # : 080100

CERAN XM 220

Date of the previous version: 2012-12-05

Revision Date: 2013-09-25

Version 1.03

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name	CERAN XM 220
Number	4KF
Pure substance/mixture	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Lubricating grease.
------------------------	---------------------

1.3. Details of the supplier of the safety data sheet

Supplier	TOTAL LUBRIFIANTS 562 Avenue du Parc de L'île 92029 Nanterre Cedex Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71
-----------------	--

For further information, please contact:

Contact Point	HSE
E-mail Address	rm.msds-lubs@total.com

1.4. Emergency telephone number

+33 1 49 00 00 49 (24h/24, 7d/7)
 France - ORFILA (INRS) Tél : +33 (0)1 45 42 59 59
 In France : - PARIS : Hôpital Fernand Widal 200, rue du Faubourg Saint-Denis 75475 Paris Cédex 10 , Tel : 01.40.05.48.48. -
 MARSEILLE : Hopital Salvator, 249 bd Ste Marguerite 13274 Marseille cedex 5, Tel : 04.91.75.25.25. - LYON : Hopital Edouard
 Herriot, 5 place d'Arsonvol, 69437 Lyon cedex 3, Tel : 04.72.11.69.11. - NANCY : Hopital central, 29 Av du Mal De Lattre de
 Tassigny, 54000 Nancy, Tel : 03.83.32.36.36 ou le SAMU : Tel (15)

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008

For the full text of the H-Statements mentioned in this Section, see Section 2.2.

DIRECTIVE 67/548/EEC or 1999/45/EC

For the full text of the R-phrases mentioned in this Section, see Section 16



SDS # : 080100

CERAN XM 220

Revision Date: 2013-09-25

Version 1.03

The substance/mixture is non-dangerous in accordance with Directive(s) 67/548/EEC with amendments and/or 1999/45/EC with amendments

Symbol(s)

Not classified***

2.2. Label elements**Labelled according to**

Not classified/No labelling required

R-phrases(s)

none***

S-phrases(s)

none***

Safety data sheet available on request.***

2.3. Other hazards**Physical-Chemical Properties**

Contaminated surfaces will be extremely slippery.

Environmental properties

Should not be released into the environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS3.2. Mixture

Chemical Name	EC-No	REACH registration No	CAS-No	Weight %	Classification (Dir. 67/548)	Classification (Reg. 1272/2008)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts***	271-529-4* **	no data available	68584-23-6	<3	Xi;R36	Eye Irrit. 2 (H319)
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.***	287-494-3* **	01-2119490234-40** *	85536-14-7	<2	C;R34 Xn;R22	Skin Corr. 1B (H314) Acute Tox. 4 (H302) ***
Sulfonic acids, petroleum, calcium salt***	263-093-9* **	no data available	61789-86-4	<2	Xi;R36	Eye Irrit. 2 (H319)
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts***	274-263-7* **	01-2119492616-28** *	70024-69-0	<2	Xi;R36	Eye Irrit. 2 (H319)

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

For the full text of the R-phrases mentioned in this Section, see Section 16

For the full text of the H-Statements mentioned in this Section, see Section 16.



SDS # : 080100

CERAN XM 220

Revision Date: 2013-09-25

Version 1.03

4. FIRST AID MEASURES**4.1. Description of first-aid measures**

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids.
Skin contact	Remove contaminated clothing and shoes. Wash skin with soap and water. Wash contaminated clothing before reuse. High pressure jets may cause skin damage. Take victim immediately to hospital.
Inhalation	Move to fresh air.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

4.2. Most important symptoms and effects, both acute and delayed

Eye contact	Not classified.
Skin contact	Not classified. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES**5.1. Extinguishing media**

Suitable Extinguishing Media	Foam. Carbon dioxide (CO ₂). ABC powder. Water spray or fog.
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special Hazard	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.
-----------------------	--



SDS # : 080100

CERAN XM 220

Revision Date: 2013-09-25

Version 1.03

5.3. Advice for fire-fighters

Special protective equipment for fire-fighters Wear self-contained breathing apparatus and protective suit.

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Collect free product with suitable mechanical means. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Personal Protective Equipment See Section 8 for more detail.

Waste treatment See section 13.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.

Prevention of fire and explosion Take precautionary measures against static discharges. Ground/bond containers, tanks and transfer/receiving equipment.

SDS # : 080100

CERAN XM 220

Revision Date: 2013-09-25

Version 1.03

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep away from food, drink and animal feedingstuffs. Keep in a banded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.

Materials to Avoid

Strong oxidizing agents.

7.3. Specific end uses

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

oil mist : 10mg/m³, for 15 minutes
oil mist : 5mg/m³, for 8 hours

Legend

See section 16

DNEL Worker (Industrial/Professional)

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts*** 68584-23-6			3.33 mg/kg bw/day (dermal) 0.66 mg/m ³ (inhalation)	
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.*** 85536-14-7			12 mg/m ³ Inhalation 170 mg/kg Dermal***	12 mg/m ³ Inhalation***
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts*** 70024-69-0			0.66 mg/m ³ Inhalation 3.33 mg/kg bw/day Dermal***	

DNEL Consumer

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
---------------	------------------------------	---------------------------	-----------------------------	--------------------------



SDS # : 080100

CERAN XM 220

Revision Date: 2013-09-25

Version 1.03

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts*** 68584-23-6			1.667 mg/kg bw/day (dermal) 0.33 mg/m ³ (inhalation) 0.8333 mg/kg bw/day (oral)	
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.*** 85536-14-7			3 mg/m ³ Inhalation 85 mg/kg Dermal 0.85 mg/kg bw/day Oral***	3 mg/m ³ Inhalation***
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts*** 70024-69-0			0.33 mg/m ³ Inhalation 1.667 mg/kg bw/day Dermal 0.8333 mg/kg bw/day Oral***	

Predicted No Effect Concentration (PNEC)

Chemical Name	Water	Sediment	Soil	Air	STP	Oral
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts*** 68584-23-6	1 mg/l fw 1 mg/l mw 10 mg/l or	723500000 mg/kg dw fw 723500000 mg/kg dw mw	868700000 mg/kg dw		100 mg/l	16.667 mg/kg food
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.*** 85536-14-7	0.287 mg/l fw 0.0287 mg/l mw 0.0167 mg/l or***	0.287 mg/kg dw fw 0.287 mg/kg dw mw***	35 mg/kg dw***		3.43 mg/l***	
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts*** 70024-69-0	1 mg/l fw 1 mg/l mw 10 mg/l or***	723500000 mg/kg dw fw 723500000 mg/kg dw mw***			100 mg/l***	16.667 mg/kg food***

8.2. Exposure controls**Occupational Exposure Controls****Engineering Measures**

Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Personal Protective Equipment**General Information**

If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.

Respiratory protection

None under normal use conditions. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.



SDS # : 080100

CERAN XM 220

Revision Date: 2013-09-25

Version 1.03

Eye Protection	If splashes are likely to occur, wear: Safety glasses with side-shields.
Skin and body protection	Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.
Hand Protection	Hydrocarbon-proof gloves: Fluorinated rubber, Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves.

Environmental exposure controls

General Information The product should not be allowed to enter drains, water courses or the soil.

9. PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Color		amber
Physical State @20°C		solid
Odor		Characteristic
<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		Not applicable
Boiling point/boiling range		Not applicable
Flash point		No information available
Evaporation rate		No information available
Flammability Limits in Air		No information available
Vapor Pressure		No information available
Vapor density		No information available
Density	~ 900 kg/m³	@ 20 °C
Water solubility		Insoluble
Solubility in other solvents		Soluble in many common organic solvents
logPow		No information available
Autoignition temperature		No information available
Viscosity, kinematic	220 mm²/s	@ 40 °C
Explosive properties	Not explosive	
Oxidizing Properties	Not applicable	
Possibility of hazardous reactions	Not applicable	

9.2. Other information

Penetration index	28 - 31 mm	I-2137
Drop point	300 °C	I-396



SDS # : 080100

CERAN XM 220

Revision Date: 2013-09-25

Version 1.03

10. STABILITY AND REACTIVITY10.1. Reactivity10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous Reactions None under normal processing.

10.4. Conditions to Avoid

Conditions to Avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.

10.5. Incompatible Materials

Materials to Avoid Strong oxidizing agents.

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products None under normal use. Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION11.1. Information on toxicological effectsAcute toxicity Local effects Product Information

Skin contact . Not classified. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent.

Eye contact . Not classified.

Inhalation . Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.

Ingestion . Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Acute toxicity - Component Information



SDS # : 080100

CERAN XM 220

Revision Date: 2013-09-25

Version 1.03

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts***	> 5000 mg/kg (Rat - OECD 401)	> 5000 mg/kg bw (rabbit - OECD 402)	> 1.9 mg/l (Rat - aerosol-OECD 403)
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.***	LD50 > 200 - 2000 mg/kg (rat - OECD 401)***		
Sulfonic acids, petroleum, calcium salt***	> 5000 mg/kg (Rat)	> 4000 mg/kg (Rabbit)	
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts***	LD50 > 5000 mg/kg (OECD 401)***	LD50 > 2000 mg/kg (OECD 402)***	

Sensitization**Sensitization**

Not classified as a sensitizer.

Specific effects**Carcinogenicity**

This product is not classified carcinogenic.

Mutagenicity

This product is not classified as mutagenic.

Reproductive toxicity

This product does not present any known or suspected reproductive hazards.

Repeated Dose Toxicity**Subchronic toxicity**

No information available.

Target Organ Effects (STOT)**Target Organ Effects (STOT)**

No information available.

Other information**Other adverse effects**

Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).

12. ECOLOGICAL INFORMATION**12.1. Toxicity**

Not classified.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts*** 68584-23-6	EL50 (72h) >1000 mg/l Pseudokirchneriella subcapitata	EL50 (48h) > 1000 mg/l daphnia magna	LL50(96h) > 10000 mg/l Cyprinodon variegatus (OECD 203)	
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.*** 85536-14-7	EC50 (72h) > 10 - 100 mg/l (Desmodesmus subspicatus - OECD 201)***	EC50 (48h) > 1 - 10 mg/l (Daphnia magna - OECD 202)***	LC50 (96h) > 1 - 10 mg/l (Cyprinus carpio - OECD 203)***	



SDS # : 080100

CERAN XM 220

Revision Date: 2013-09-25

Version 1.03

Sulfonic acids, petroleum, calcium salt*** 61789-86-4		EC50 (48h) > 100 mg/l Daphnia magna (OECD 202)	LC50 (96h) > 10000 mg/l Cyprinodon variegatus (OECD 203)	
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts*** 70024-69-0	EC50 (72h) > 1000 mg/l (Pseudokirchnerella subcapitata - static)***	EC50 (48h) > 1000 mg/l (Daphnia magna - static)***	LL50 (96h) > 10000 mg/l (Cyprinodon variegatus - OECD 203)***	

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

No information available.

Effects on terrestrial organisms

No information available.

12.2. Persistence and degradability**General Information**

No information available.

12.3. Bioaccumulative potential**Product Information**

No information available.

logPow

No information available

Component Information

Chemical Name	log Pow
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.*** - 85536-14-7	2***

12.4. Mobility in soil**Soil**

Given its physical and chemical characteristics, the product has no soil mobility.

Air

Loss by evaporation is limited.

Water

The product is insoluble and floats on water.

12.5. Results of PBT and vPvB assessment**PBT and vPvB assessment**

No information available.

12.6. Other adverse effects**General Information**

No information available.



SDS # : 080100

CERAN XM 220

Revision Date: 2013-09-25

Version 1.03

13. DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods**

Waste from Residues / Unused Products	Should not be released into the environment. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
EWC Waste Disposal No.	The following Waste Codes are only suggestions: 12 01 12. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

14. TRANSPORT INFORMATION

<u>ADR/RID</u>	Not regulated
<u>IMDG/IMO</u>	Not regulated
<u>ICAO/IATA</u>	Not regulated
<u>ADN</u>	Not regulated

15. REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

European Union

International Inventories

EINECS/ELINCS	-
TSCA	-
DSL	-
ENCS	-
IECSC	-
KECL	-
PICCS	-
AICS	-
NZIoC	-



SDS # : 080100

CERAN XM 220

Revision Date: 2013-09-25

Version 1.03

Legend**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List**ENCS** - Japan Existing and New Chemical Substances**IECSC** - China Inventory of Existing Chemical Substances**KECL** - Korean Existing and Evaluated Chemical Substances**PICCS** - Philippines Inventory of Chemicals and Chemical Substances**AICS** - Australian Inventory of Chemical Substances**NZIoC** - New Zealand Inventory of Chemicals

Further information

15.2. Chemical Safety Assessment**Chemical Safety Assessment** No information available**16. OTHER INFORMATION****Full text of R-phrases referred to under sections 2 and 3**

R36 - Irritating to eyes

R61 - May cause harm to the unborn child

R60 - May impair fertility

R34 - Causes burns

R22 - Harmful if swallowed***

Full text of H-Statements referred to under sections 2 and 3

H319 - Causes serious eye irritation

H314 - Causes severe skin burns and eye damage

H302 - Harmful if swallowed***

Abbreviations, acronyms**Legend Section 8**

+	Sensitizer	*	Skin designation
**	Hazard Designation	C:	Carcinogen
M:	Mutagen	R:	Toxic to reproduction

Revision Date: 2013-09-25**Revision Note** *** Indicates updated section.**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**



SDS # : 080100

CERAN XM 220

Revision Date: 2013-09-25**Version** 1.03

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the safety data sheet